








































Tab1. ZESTAWIENIE STUDIŃ ZKRĘGÓW DN1000 BETONOWYCH LUB Ø1000 PP/PEHD/PVC

Nr studni	Schemat kinety	Średnica				Rzędna					Kąty				
		Odpływu	Dopływu				Terenu	Posadowienia dna rury							
			D	D1	D2	D3		R ₁	R _D	R _{D1}	R _{D2}	R _{D3}	R ₁ -R _D	α ₁	α ₂
		[mm]	[mm]	[mm]	[mm]	[m.nm]	[m.nm]	[m.nm]	[m.nm]	[m.nm]	[m]	(°)	(°)	(°)	
S1.1		200	200	160	160	145.90	144.00	144.00	144.00			1.90	90	180	270
S1.2		200	200	160	-	146.30	143.75	143.75	143.75			2.55	180	270	-
S1.3		200	200	160	-	146.54	143.52	143.52	143.52			3.02	180	270	-
S1.4		200	200	160	-	146.30	143.28	143.28	143.28			3.02	180	270	-
S1.5		200	200	-	-	145.90	143.04	143.04				2.86	180	-	-
S1.6		200	200	160	-	144.90	142.79	142.79	142.79			2.11	90	180	-
S1.7		200	200	-	-	144.50	142.50	142.50				2.00	180	-	-
S1.8		200	200	160	200	143.65	141.65	141.65	141.65			2.00	90	180	270
S1.9		200	200	160	-	143.10	140.11	141.21	141.21			2.99	90	180	-
S1.10		200	200	160	-	142.40	139.86	139.86	139.86			2.54	90	180	-
S1.11		200	200	200	200	141.80	139.61	139.61				2.19	90	180	270
S1.12		200	200	160	-	141.60	139.36	139.36	139.36			2.24	90	180	-
S1.13		200	200	-	-	142.00	139.12					2.88	270	-	-
S1.14		200	200	160		141.70	138.87	138.87	138.87			2.83	90	180	
S1.15		200	200	160	160	141.40	138.72	138.72	138.72			2.68	90	180	270
S1.16		200	200	200	-	141.15	138.54	138.54	138.54			2.55	186	270	-
S1.17		200	200	200	-	141.16	138.50	138.50	139.30			2.66	91	268	-
S1.18		200	200		-	141.58	138.25	138.25				3.33	180		-
S1.19		200	200		-	142.10	138.11	138.11				3.99	180		-
S3.1		200	200		-	140.50	139.27	139.28				1.23	90		-
S3.2		200	200	200		140.78	139.09	139.09	139.09			1.69	90	180	
S3.3		200	200	200	-	140.83	138.91	138.91	138.91			1.92	90	180	-
S3.4		200	200	160		141.00	138.65	138.65	138.65			2.35	96	173	-
S4.1		200	200	160	-	142.75	140.84	140.84	140.84			1.86	90	270	-
S4.2		200	200	160	-	142.40	140.65	140.65	140.65			1.75	180	270	-
S4.3		200	200	160	-	142.20	140.45	140.45	140.45			1.75	90	180	-
S4.4		200	200	160	-	141.70	140.10	140.10	140.10			1.60	90	180	-
S4.5		200	200	160	160	141.53	139.87	139.87	139.87	139.87		1.66	90	180	270
S4.6		200	200	160		141.25	139.54	139.54	139.54			1.71	94	174	
S5.1		200	200		-	145.70	144.49	144.49				1.21	180	90	270
S5.2		200	200		-	145.30	144.24	144.24				1.06	180	270	-
S5.3		200	200			145.00	143.99	143.99				1.01	180	90	270
S5.4		200	200		-	144.70	143.74	143.74				0.96	180	90	270
S6.1		200	160/160	160	160	144.60	143.26	143.26	143.26	143.26		1.34	90/145	220	270
S6.2		200	200			144.50	143.01	143.01				1.49	180		
S7.1		200	160	160		145.10	143.19	143.19	143.19			1.91	90	270	
S7.2		200	200		-	144.40	142.94	142.94				1.46	180		
S7.3		200	200	160	160	144.10	142.68	142.68	142.68	142.68		1.42	90	180	270
S7.4		200	200	160	160	143.90	142.44	142.44	142.44	142.44		1.46	90	180	270
S7.5		200	200	160	160	143.51	142.19	142.19	142.19	142.19		1.32	90	180	270
S7.6		200	160	200	160	143.70	141.97	141.97	141.97	142.19		1.73	90	180	270
S7.7		200	200		-	143.70	141.80	141.80				1.90	180		-
S7.8		200	200	160	-	143.75	141.64	141.64	141.64			2.11	137	227	-
S7.9		200	200		-	143.75	141.61	141.61				2.14	223		-
S7.10		200	200		-	144.10	141.44	141.44				2.66	180		-
S8.1		200	160	160		143.33	142.15	142.15	142.15			1.18	90	270	
S9.1		200	160	160	160	142.85	140.98	140.98	140.98	140.98		1.87	90	123	180
S9.2		200	200	160	-	142.70	140.81	140.81	140.81			1.89	90	180	-
S9.3		200	200		-	142.70	140.67	140.67				2.03	180		-
S9.4		200	200		-	142.									

Tab2. ELEMENTY BETONOWE PREFABRYKOWANE

Nr	Element	Ilość
1	Dolna część studni – złącze z uszczelką DN1000, z kłosem,	1
2	Krąg betonowy DN1000, h=300mm, złącze z uszczelką	1
3	Zwężka redukcyjna 1000/ 625 x 600	1
4	Pierścień dystansowy 625 x 60	1

Tab3. ELEMENTY DO OSADZENIA DLA JEDNEJ STUDZIENKI BETONOWEJ